SHOP LIFTERS & STACKERS

WINCH OPERATED

- Ideal for use in factory, office or shipping department
- Can perform numerous functions from lifting objects to positioning products at best working height, to moving light loads without tying up heavy equipment
- Manoeuvres easily in areas too narrow for a lift truck
- Two swivel casters under forks allow the shop lifter to do a 360° turn on twice the length of the base

SPECIFICATIONS:



casters allow loads

to be moved easily

HYDRAULIC

Allows workers to manoeuver

to comfortable needed height

Stacker comes standard with

and lift heavy loads safely

floor locks, safety screen

and foot guards for safety

Front 5" and rear 4" phenolic

STACKER

SPECIFICATIONS:

Capacity:	1000 lbs. at 15" load center
Overall dimensi	ons:25.5" W x 40" D x 80" H
Platform size: .	
Lowered platfor	m height:5.75"
Raised platform	height:
Base legs:	15" inner, 21" outer
Wheels:	5" front, 4" rear
Weight:	
Model No. MH	690

1000-LB. CAPACITY

750-LB. HYDRAULIC STACKER

- · Front swivel casters eliminate need to break the load, making handling and
- load positioning easier Easily manoeuvrable
- in narrow aisles Each downstroke lifts 1" with only 60 lbs. of effort needed to lift 750 lbs.
- Foot pedal folds safely out of the way with magnetic retention



212124

Raised Height -

Raised Height

SPECIFICATIONS:

Overall Height Forks Raised/Lowered

Capacity:
Overall height:
Platform size:
Lowered platform height: 5 3/4
Lift above floor:
Wheels:8" mould-on rubbe
Casters: polyurethane 3 1/2" diamete
Weight:
Model No. MA429

HYDRAULIC STACKERS

Capacity:500 lbs. at 10" load centre Overall height:60" Wheels:6" diameter Casters:3" diameter

- · Rugged frame construction
- Solid steel adjustable forks
- Designed for pallet loading and removal from racking storage even in the smallest storage spaces
- Straddle length: 30.5"
- · Fork length: 48"

Model No. MA479

- · Load center: 24"
- · Manually propelled with electric powered hydraulic lift
- Battery powered is standard (AC power and air power available)
- Automatic built-in battery charger included

Please specify when ordering:

Inside straddle dimension: Between 42" and 50" Note: Inside straddle dimension is recommended to be 2" greater than the overall pallet width (outside straddle is 6" greater than

straddle inside dimension)

SINGLE STAGE STACKERS


Model No.	Clearance of top mast"	Raised height of top forks"	Capacity lbs.	Wt. Ibs.
MH738	82	68	1500	720
MH739	87	68	2000	730
MH740	87	68	2500	850
MH741	104	90	1500	720
MH742	109	90	2000	730

TELESCOPIC

(TWO STAGE) STACKERS

Model	Top of	f Mast	Raised height	Capacity	Wt.
No.	Lowered"	Raised"	of top forks"	lbs.	lbs.
MH743	88	154	132	1500	1020
MH744	88	154	132	2000	1030
MH745	93	159	132	2500	1150
MH746	94	166	144	1500	1170
MH747	94	166	144	2000	1180

Other fork length available (36" or 42")





REEL DISPENSER

- For winding or dispensing cable, chain, wire, rope and hose
- Turns reel handling into a one person operation
- Accommodates unlimited reel widths and all reel diameters, flanges up to 5 1/2" thick
- · Rear roller adjusts to 6 positions
- · Heavy-duty side rollers eliminate slipping or wedging between rollers and reel
- Inclined ramp permits easy loading and unloading
- Measures 28" L x 9 1/4" W x 4" H
- 3000 lbs. capacity in pairs · Weight: 58 lbs/pair

Model No. MD166







B76

22654E