PALLET HANDLING EQUIPMENT


WESCO*

ADJUSTABLE WIDTH PALLET TRUCK

Fork width adjusts from 21" to 27'

- Fork length: 46"
- 7" mould-on polyurethane steering wheel
- 3" mould-on polyurethane load wheels
- Raised height: 7.75'
- Lowered height: 3"
- Forks width: 6"
- Capacity: 5,500 lbs

Model No. MI820



TRANSROLLER PALLET TRUCK

- · Move loads forward and backward as well as side to side
- Fork spacing is 27" wide and 48" in length 7" wide forks include entry rollers
- and 3" mold-on load wheels
- 8" mold-on polyurethane steering wheels · Lowered height: 3.4"; raised height: 8.5"
- Capacity: 5000 lbs. in standard mode

and 2200 lbs. in lateral mode

Model No. MJ550





POWER-START TECHNOLOGY™ PALLET TRUCK


The right tool for ergonomic pallet motion!

- Reduces starting resistance even when truck is heavily loaded
- Select travel direction via option on handgrip, squeeze the handgrip, pump the tow bar and the truck is launched in the walking direction
- When handgrip is pressed downward, and tow bar raised, the truck is launched in the direction of the forks

Specifications:

- Forks: 27" x 48" Minimum fork height: 3"
- Maximum fork height: 7.5"
- Rated capacity: 5000 lbs.
- Weight: 188 lbs.

Model No. MH736



LIMITED VFΔR

LIFERITE.

PALLET **JACK STOP**

- · Ideal solution to reducing freight claims and trailer damage caused by runaway pallet trucks
- Engineered for tough duty
- inside trucks and trailers The pallet jack stop functions
- on any surface without slipping Simple to use, just roll the pallet
- trucks steering wheels up the incline into the holding area Weight: 3.5 lbs.
- Model No. MK832





LIFT-RITE® TITAN PALLET TRUCKS

- New one-piece pump for improved performance and reliability
- Includes ergonomic handles and articulating steering wheels
- 3" fork lowered height, 7 3/4" fork raised height
- 7" fork width
- · Capacity: 5,500 lbs.

Model	Frame	Fork Length" 36	Wt. Ibs.
No	Width"		
ML052	20.5	36	142
ML053	20.5	42	147
ML054	20.5	48	152
ML055	27	36	147
ML056	27	42	157
ML057	27	48	167

Note: Custom Sizes Available



YEAR VARRANTY

LOW PROFILE LIFT-RITE® HYDRAULIC LIMITED

PALLET TRUCKS Capacity: 5000 lbs

Polyurethane wheels and steel rollers

CIFFRITE Model Fork lowered Raised Fork Wt. Width" Length" lbs. Height" Height" MH734 175 27 6.3/4 48 1 3/4 MH735 6 1/2 27 175

Note: Ultra low profile available

ERGONOMIC PALLET TILTER

- Reliable pallet tilter allows users to tilt and lift pallets to a more convenient and safe work position
- 5" polyurethane steering wheels combined with 3" polyurethane load wheels for mobility
- Forks tilt up to 90° for accurate load positioning
- Lifting range with forks in horizontal position: 3 1/4" to 11"
- Lifting range with backrest in horizontal position: 29" to 37"
- Load center: minimum 7 1/2", maximum 15 1/2"
- 6 1/2" forks are spaced 21 1/2" wide by 31" in length
- Total capacity: 2,200 lbs.
- Weight: 393 lbs.
- 1 year manufacturer's pump warranty

Model No. MK824





4-WAY LIFT-RITE® **HYDRAULIC** PALLET TRUCK

- 2" fork lowered height, 6 3/4" fork raised height
- 6" wide forks
- Capacity: 5000 lbs.

Model	Frame	Fork	Wt.
No.	Width"	Length"	Ibs.
MH737	33	48	205



B78