PACKAGING SUPPLIES

POLYPROPYLENE STRAPPING SEALERS

· Heat treated steel construction for superior strength and durability Prevents strapping from

loosening during transit Long 18" handle requires

Model No.	Strap Width"
PA555	1/2
PA556	5/8

less effort



SAFETY CUTTERS FOR STEEL STRAPPING STANDARD-DUTY Cuts steel strapping 3/8-1 1/4" wide x .036" thick Safety design holds strapping in place to prevent injuries from flying ends Rubber pads gently release strapping when being cut Model No. PC446

HEAVY-DUTY

- · Cuts steel strapping 3/8-2" wide x .050" thick
- Powerful drop-forged steel design
- · Heavy-duty performance for industrial applications



POLYPROPYLENE & POLYESTER STRAPPING TENSIONER

• Ideal for applications on flat surfaces

- Accepts strapping 3/8 -3/4" wide
- · Superior design and performance
- · Premium copper bushings
- Built-in strapping cutter

· For use with open seals or buckles

Model No. PC939





STEEL & POLYSTRAP **DISPENSERS**

· Positive brake on reel prevents over-run tangled coils

- Basket
- · Rubber wheels

For use with 16" x 3" or 16" x 6" POLY or STEEL coils. 54 lbs.

Model No. PA568

For use with 8" x 8" POLY coils. 34 lbs.

Model No. PA569



STEEL STRAPPING TENSIONERS



PUSH BAR STYLE

- Ideal for applications on small. round or irregular surfaces
- Accepts steel strapping 3/8-1/2" wide x 0.020" thick
- Light tension
- Limited take-up
- For use with push type seals



FEED-WHEEL STYLE

- Ideal for applications on flat surfaces
- Accepts steel strapping 3/8-3/4" wide x 0.035" thick
- Fast and easy operation
- Medium/heavy tension
- Unlimited take-up
- · For use with open seals

Model		Strap	
No.	Description	Width"	
PA567	Push Bar	3/8 to 1/2	
PC938	Standard	3/8 to 3/4	

SELF DISPENSING **POLY STRAP** CARTON WITH **BUCKLES**

- Hand strap large or small packages of all shapes
- Comes complete with polypropylene strapping and steel buckles



Model No.	Strap Width"	Strength/lbs.	Feet/ctn.	Buckles/ctn.
PA514	1/2	300	3300	200

STEEL STRAPPING SEALERS

- · For use with open seals
- Double notch creates a strong interlocking joint
- Heat-treated steel construction for added durability
- Ideal for use with feed-wheel style tensioners
- Ball handles provide a superior grip



Model No.	Width"
PA550	1/2
PA562	5/8
PA551	3/4

22573E **B138**