PALLET TRUCKS



Rugged construction makes this pallet truck the best value for your material handling needs. Up to 27" W x 48" L forks feature entry rollers and tapered design for easy pallet entry and are reinforced for heavy-duty loads. The 3-function hand control (raise, neutral and lower) and the spring-loaded self-righting safety loop handle enhance comfort and ease of operation. Hardened chrome piston with protective dust cover for dependable performance. Durable powder coat finish.



HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- Maintenance-free sealed bearings at all pivot points
- 6" (152 mm) wide forks
- Colour: High visibility orange
- Meets CE standards
- · 1-year pump warranty

| | Pallet Truck Height | | Fork | Fork | |
|--------------|---------------------|---------------|--------------|---------------|------------------|
| Model No. | Lowered in" | Raised in" | Width in" | Length in" | Capacity Ibs. |
| MJ484 | 2 7/8 | 7 3/4 | 20 1/2 | 36 | 5500 |
| MJ485 | 2 7/8 | 7 3/4 | 20 1/2 | 42 | 5500 |
| MJ486 | 2 7/8 | 7 3/4 | 20 1/2 | 48 | 5500 |
| MJ487 | 2 7/8 | 7 3/4 | 27 | 36 | 5500 |
| MJ488 | 2 7/8 | 7 3/4 | 27 | 42 | 5500 |
| MJ489 | 2 7/8 | 7 3/4 | 27 | 48 | 5500 |



HEAVY-DUTY HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- Double rollers for easy moving of extra heavy loads
- · Reinforced fork channels deliver exceptional durability
- 6" (152 mm) wide forks
- · Colour: Kleton blue
- Meets CE standards
- · 2-year pump warranty

| | Pallet Truck Height | | Fork | Fork | |
|-------|---------------------|--------|--------|--------|----------|
| Model | Lowered | Raised | Width | Length | Capacity |
| No. | in" | in" | in" | in" | lbs. |
| MJ490 | 2 7/8 | 7 3/4 | 20 1/2 | 36 | 6600 |
| MJ491 | 2 7/8 | 7 3/4 | 20 1/2 | 42 | 6600 |
| MJ492 | 2 7/8 | 7 3/4 | 20 1/2 | 48 | 6600 |
| MJ493 | 2 7/8 | 7 3/4 | 27 | 36 | 6600 |
| MJ494 | 2 7/8 | 7 3/4 | 27 | 42 | 6600 |
| MJ495 | 2 7/8 | 7 3/4 | 27 | 48 | 6600 |



18969E **B77**

PALLET HANDLING EQUIPMENT

SKID LIFTS

- · Allows entry into different skids and baskets
- · Lightweight design is easy to manoeuver with pallet truck style steering configuration
- · Strong and reliable cylinder
- Quick-lift mechanism on manual lifts allows loads under 400 lbs.
- to be raised with 24 strokes, heavier loads require 72 strokes
- Self-contained battery powered power pack (electric models) eliminates power source or power cord problems
- · Built-in automatic battery charger and charge indicator (electric models)
- Raised bulkhead design provides greater backrest surface, ergonomic location for automatic battery charger and clear view of load
- 24" load center
- · Lowered height: 3 1/4", raised height: 31 1/2"
- · 8" polyurethane load wheels and 3" polyurethane load roller
- · Capacity: 3000 lbs.

| Model No. | Dim | of fo | rks" | Wt. Ibs. | | |
|--------------|------|-------|------|----------|--|--|
| MANUAL LIFTS | | | | | | |
| MH748 | 20.5 | Х | 48 | 330 | | |
| MH749 | 27 | Х | 48 | 340 | | |

| Model No. | Dim | of fo | rks" | Wt. lbs. | |
|------------|-------|-------|------|----------|--|
| ELECTRIC I | LIFTS | | | | |
| MH796 | 20.5 | Х | 48 | 430 | |
| MH797 | 27 | x | 48 | 440 | |



GALVANIZED PLATED PALLET TRUCK

- · Designed to withstand corrosive and wet environments
- Ideal for use in chemical, pharmaceutical and wash-down applications
- Steering and load wheels are made of nylon to provide durability in cold environments
- · Fork length: 48"
- · Overall fork width: 27
- · Load capacity: 5,500 lbs.
- Lowered fork height: 2 7/8"
- · Raised fork height: 7 3/4"
- · Weight: 327 lbs.
- · Not approved for clean rooms

Model No. MK830





FORK EXTENSIONS

- Handle large and odd shaped loads with increased stability and minimum damage
- Available in 4", 5" and 6" fork widths, lengths are from 54" to 96"
- Easy to use slide-on design
- Fork fits up to 2" thick
- Convenient on/off design
- Locking bar keeps extensions in place
- Fork extension not to exceed 50% more than existing fork





| Model No. | Accommodates Fork Width" | Fork Extension Overall Width" | Length" | Max. Fork Thickness" | Wt. |
|--------------|-----------------------------|----------------------------------|---------|-------------------------|-----|
| | | | | | |
| MF775 | 4 | 5 | 54 | 2 | 109 |
| MF776 | 4 | 5 | 63 | 2 | 125 |
| MF777 | 4 | 5 | 72 | 2 | 135 |
| MF778 | 4 | 5 | 84 | 2 | 157 |
| MF779 | 4 | 5 | 96 | 2 | 173 |
| MF781 | 5 | 6 | 54 | 2 | 126 |
| MF782 | 5 | 6 | 63 | 2 | 151 |
| MF783 | 5 | 6 | 72 | 2 | 155 |
| MF784 | 5 | 6 | 84 | 2 | 189 |
| MF785 | 5 | 6 | 96 | 2 | 201 |
| MF787 | 6 | 7 | 54 | 2 1/2 | 146 |
| MF788 | 6 | 7 | 63 | 2 1/2 | 165 |
| MF789 | 6 | 7 | 72 | 2 1/2 | 166 |
| MF790 | 6 | 7 | 84 | 2 1/2 | 199 |
| MF791 | 6 | 7 | 96 | 2 1/2 | 210 |

Also available: Add-on for optional pins style fork extension and other lengths.

STAINLESS STEEL PALLET TRUCKS



- Ideal for sanitary, pharmaceutical, medical, food and wet applications
 Available with the page.
- Available with type 304 stainless steel frames and forks or complete stainless steel construction
- Complete stainless steel units are ideal for food service when combined with foodapproved hydraulic oil
- All models feature nylon steering and load wheels
- Fork height: 2 7/8" minimum, 7 3/4" maximum
- Capacity: 5,500 lbs.
- Not approved for clean rooms

| Model | | Overall Fork D | Wt. | |
|-------|---------------------------------|----------------|---------|------|
| No. | Description | Width" | Length" | lbs. |
| MK827 | Stainless Steel Frame and Forks | 27 | 48 | 285 |
| MK828 | Complete Stainless Steel | 27 | 48 | 285 |
| MK829 | Complete Stainless Steel | 20 | 48 | 300 |

CAROUSEL PALLET TURNTABLES

Loading and unloading operations that originally required a large amount of time can be done more efficiently with less fatigue and risk of back injury. The carousel may be added to an existing workbench, scissors table or simply placed on the floor. This Lazy Susan concept is constructed from two pieces of rolled structural angle. A series of roller bearings transfer the load smoothly and evenly to the supporting surface.

Overall height is 2 1/4".







| Model | Outside | Capacity | Wt. | |
|-------|-----------|----------|------|--|
| No. | Diameter" | lbs. | lbs. | |
| MH204 | 40 | 2000 | 40 | |
| MH205 | 40 | 4000 | 44 | |
| MH206 | 40 | 6000 | 48 | |
| MH207 | 48 | 2000 | 48 | |
| MH208 | 48 | 4000 | 51 | |
| MH209 | 48 | 6000 | 55 | |

PALLET HANDLING EQUIPMENT


WESCO*

ADJUSTABLE WIDTH PALLET TRUCK

Fork width adjusts from 21" to 27'

- Fork length: 46"
- 7" mould-on polyurethane steering wheel
- 3" mould-on polyurethane load wheels
- Raised height: 7.75'
- Lowered height: 3"
- Forks width: 6"
- Capacity: 5,500 lbs

Model No. MI820



TRANSROLLER PALLET TRUCK

- · Move loads forward and backward as well as side to side
- Fork spacing is 27" wide and 48" in length 7" wide forks include entry rollers
- and 3" mold-on load wheels
- 8" mold-on polyurethane steering wheels · Lowered height: 3.4"; raised height: 8.5"
- Capacity: 5000 lbs. in standard mode

and 2200 lbs. in lateral mode Model No. MJ550



POWER-START TECHNOLOGY™ PALLET TRUCK


The right tool for ergonomic pallet motion!

- Reduces starting resistance even when truck is heavily loaded
- Select travel direction via option on handgrip, squeeze the handgrip, pump the tow bar and the truck is launched in the walking direction
- When handgrip is pressed downward, and tow bar raised, the truck is launched in the direction of the forks

Specifications:

- Forks: 27" x 48" Minimum fork height: 3"
- Maximum fork height: 7.5"
- Rated capacity: 5000 lbs.
- Weight: 188 lbs.

Model No. MH736



LIMITED

PALLET **JACK STOP**

- · Ideal solution to reducing freight claims and trailer damage caused by runaway pallet trucks
- Engineered for tough duty inside trucks and trailers
- The pallet jack stop functions on any surface without slipping
- Simple to use, just roll the pallet trucks steering wheels up the incline into the holding area
- Weight: 3.5 lbs.

Model No. MK832






New one-piece pump for improved performance and reliability

LIFERITE.

- articulating steering wheels
- 3" fork lowered height, 7 3/4" fork raised height
- 7" fork width
- · Capacity: 5,500 lbs.

| Model | Frame | Fork | Wt. | |
|-------|--------|---------|------|--|
| No | Width" | Length" | lbs. | |
| ML052 | 20.5 | 36 | 142 | |
| ML053 | 20.5 | 42 | 147 | |
| ML054 | 20.5 | 48 | 152 | |
| ML055 | 27 | 36 | 147 | |
| ML056 | 27 | 42 | 157 | |
| ML057 | 27 | 48 | 167 | |

LIFT-RITE® TITAN PALLET TRUCKS Includes ergonomic handles and




YEAR VARRANTY



LOW PROFILE LIFT-RITE® HYDRAULIC LIMITED **PALLET TRUCKS**

- Capacity: 5000 lbs
- Polyurethane wheels and steel rollers



ERGONOMIC PALLET TILTER

- Reliable pallet tilter allows users to tilt and lift pallets to a more convenient and safe work position
- 5" polyurethane steering wheels combined with 3" polyurethane load wheels for mobility
- Forks tilt up to 90° for accurate load positioning
- Lifting range with forks in horizontal position: 3 1/4" to 11"
- Lifting range with backrest in horizontal position: 29" to 37" Load center:
- minimum 7 1/2", maximum 15 1/2"
- 6 1/2" forks are spaced 21 1/2" wide by 31" in length
- Total capacity: 2,200 lbs.
- Weight: 393 lbs.
- 1 year manufacturer's pump warranty

Model No. MK824





4-WAY LIFT-RITE® **HYDRAULIC** PALLET TRUCK

- 2" fork lowered height, 6 3/4" fork raised height
- 6" wide forks
- Capacity: 5000 lbs.

| Model | Frame | Fork | Wt. |
|-------|--------|---------|------|
| No. | Width" | Length" | Ibs. |
| MH737 | 33 | 48 | 205 |



B78