DRUM LIFTERS

DRUM/OVERPACK LIFTERS

- A safe method of moving 45-gallon steel drums
- Design allows for quick, gentle loading. Drum stays upright during lift
- Low-profile clamp design on 45-gallon lifter lowers open (lid must be on) or closed head steel drums all the way to bottom of overpack
- 70-gallon overpack lifter picks up both 70-gallon steel overpack drums and 45-gallon steel drums
- Universal model DA876 handles many lever-lock closure fibre drums typical steel drums and 45-gallon rimmed plastic drums
- Capacity: 1000 lbs.

Model		Wt.
No.	Description	lbs.
DA224	45-gal. Lifter	21
DA225	70-gal. Overpack/45-gal. Lifter	22
DA876	Universal Lifter	25
DC094	Stainless Steel Universal Lifter	25



HORIZONTAL DRUM LIFTING HOOKS


- · Horizontally lifts 45-gal. steel drums, 34"- 36" long
- · Alloy steel lifting ring, steel rods, malleable iron hooks
- Capacity: 1000 lbs.
- · Weight: 5 lbs.

Model No. DA164

- · Spark resistant lifting hook is made of bronze and copper for safe handling
- · Capacity: 1000 lbs.
- · Weight: 5 lbs.

Model No. DA163





FORK LIFT *ATTACHMENT*

- · Converts any lift truck to a below-the-hook carrier
- 360° rotation safety hook for safe, easy lifting
- · All steel construction
- Dimensions: 14" L x 31" W x 7" H
- · Capacity: 1000 lbs.
- Wt.: 42 lbs.

Model No. DA231



SINGLE FORK HOOKS

- · Convert forklift to a hoist in seconds
- · Feature a safety latch and all-welded steel frame
- Available with fixed or swivel hook



Fixed Hook Model No.	Swivel Hook Model No.	Work Load Limit, Ibs.	Fork Pocket W" x H"	Hook Opening"	Wt. lbs.
DA167	DA688	3000	4 3/8 x 2 3/8	27/32	13
DA168	DA689	3000	5 3/8 x 2 3/8	27/32	15
DA169	DA690	3000	6 3/8 x 2 3/8	27/32	16

/6500

AUTO-GRIP DRUM LIFTER

- · Easy, no-tilt lifting of rimmed steel drums
- · Self-energizing: the heavier the load, the tighter the grip
- · Attaches to any hoist, crane or forklift using single fork hook attachment
- · Heavy-duty, annealed, ductile iron construction
- · Large curved foot at bottom of stabilizing arm prevents drum damage
- · Capacity: 3000 lbs. Wt.: 31 lbs.

Model No. DA226




AUTOMATIC VERTICAL DRUM LIFTER

- · Lifts and transports closed steel drums easily and effectively
- Unit grips automatically; releases only when drum is set down
- Operator does not have to be at pick up or drop points
- 45-gallon model is available in standard steel or type 304 stainless steel construction
- Capacity: 1000 lbs.



Model No.	Lifts Drum Size Gallons	Construction Material	Wt. lbs.
DC091	30	Steel	45
DA203	45	Steel	50
DC092 DC093	45 85	Stainless Steel Steel	50 59
D 0000	00	Otto	55



REINFORCED NYLON **DRUM SLING**

- · Securely and economically lifts steel, plastic and fibre drums from 12" to 24" in diameter
- Ideal for use with a forklift truck
- Compact size of sling allows it to be stored in truck until it's needed
- Reduces drum damage which occurs when using steel handlers
- Steel ratchet tightens the reinforced nylon lifting belt around body of the barrel holding it securely in place
- 4" wide, double stitched carrying strap on the belt slips easily over the truck forks
- Capacity: 1000 lbs.
 Wt.: 5 lbs.

Note: Open ratchet fully when installing sling on 45-gal. drums.





as a wrench for use on different drum plugs, faucets, and rim ring bolts. Lifts drums up to 800 lbs capacity

- · Powder coat finish for durability
- Wt.: 20 lbs.

Model No. DC095





MANUAL VERTICAL DRUM LIFTER

- · Allows raising and moving of closed-head 45-gallon steel drums
- 1 1/2" diameter lifting eye is mounted above 4 hot rolled steel supports · Safety lock pin prevents accidental opening
- · Attaches to overhead crane or hoist
- Dimensions: 23" W x 28 1/4" D x 13 1/2" H
- · Capacity: 700 lbs.
- · Wt.: 15 lbs.
- Model No. DA228








CHAIN & NYLON LIFTING SLINGS

CHAIN SLINGS

- Quality grade 80 alloy steel assembled, feature a design factor of 4:1
- · Proof tested and certified to twice the working load limit
- · Proof test certificate issued with each sling
- Available with sling hook (SOS, DOS) or grab hook (SOG, DOG)
- Three and four leg assemblies are available upon request
- · Slings come with identification tag indicating size, description and working load limit

Chain size"	Туре	Sling Length 5' Model No.	Sling Length 8' Model No.	Sling Length 10' Model No.
9/32	SOS	LS486	LS494	LS502
	SOG	LS487	LS495	LS503
3/8	SOS	LS488	LS496	LS504
	SOG	LS489	LS497	LS505
1/2	SOS	LS490	LS498	LS506
	SOG	LS491	LS499	LS507
5/8	SOS	LS492	LS500	LS508
	SOG	LS493	LS501	LS509
9/32	DOS	LS510	LS518	LS526
	DOG	LS511	LS519	LS527
3/8	DOS	LS512	LS520	LS528
	DOG	LS513	LS521	LS529
1/2	DOS	LS514	LS522	LS530
	DOG	LS515	LS523	LS531
5/8	DOS	LS516	LS524	LS532
	DOG	LS517	LS525	LS533



NYLON SLINGS

All Uni-Web nylon slings are rated with a 5:1 design factor. Used in conjunction with overhead cranes, hoists or winches. Nylon slings are available in single or double ply to protect heavy, irregular sized loads from scratching or marring. Slings must be checked frequently. Should any surface area show signs of wear or cutting, the sling must be replaced immediately. Each is tagged with manufactured date and capacity.

TYPE 1 CHOKER SLING

- Forged alloy end fittings triangle at one end, choker at the other
- Webbing forms a slip noose by slipping the triangle through the choker

TYPE 2 TRIANGLE SLING

- Forged alloy end fittings for single or double sling basket hitches
- Soft webbing conforms to the load shape without damaging painted or polished surfaces



TYPE 3 DOUBLE EYE SLING


- · Commonly used as a basket and/or choker hitch
- For choker hitch pass one eye through the other flat eye, also makes for easy withdrawal from beneath loads

TYPE 4 REVERSE EYE SLING

- · Reverse eves make full functional contact with lifting hooks without the use of hardware
- · Widely used for both choker and basket hitches

TYPE 5 ENDLESS SLING

- · Most versatile and widely used sling
- · The economical answer to most lifting problems
- · Ideal for vertical, choker, and basket hitches



Time	
IVDE	

LOAD LIMI	T FOR TYPE	1-2-3-4					LOAD LIN	IIT FOR TYPE 5				
Capacity Ib	os.						Capacity	lbs.				
Vertical Choker Basket						Vert	tical	Ch	oker	Bas	ket	
Width"	Single	Double	Single	Double	Single	Double	Single	Double	Single	Double	Single	Double
1	1600	3200	1280	2560	3200	6400	3200	6100	2560	4880	6400	12200
2	3200	5600	2560	4480	6400	11200	5600	10600	4480	8480	11200	21200
3	4800	8400	3840	6720	9600	16800	8400	16000	6720	12800	16800	32000
4	6400	11200	5120	8960	12800	22400	11200	20200	8960	16160	22400	40400

			3' Model	4' Model	6' Model	8' Model	10' Model	12' Model
	Width"	Ply	No.	No.	No.	No.	No.	No.
TYPE 1	2	Single	LS270	LS276	LS282	LS288	LS294	LS300
		Double	LS271	LS277	LS283	LS289	LS295	LS301
	3	Single	LS272	LS278	LS284	LS290	LS296	LS302
		Double	LS273	LS279	LS285	LS291	LS297	LS303
	4	Single	LS274	LS280	LS286	LS292	LS298	LS304
		Double	LS275	LS281	LS287	LS293	LS299	LS305
TYPE 2	2	Single	LS306	LS312	LS318	LS324	LS330	LS336
		Double	LS307	LS313	LS319	LS325	LS331	LS337
	3	Single	LS308	LS314	LS320	LS326	LS332	LS338
		Double	LS309	LS315	LS321	LS327	LS333	LS339
	4	Single	LS310	LS316	LS322	LS328	LS334	LS340
		Double	LS311	LS317	LS323	LS329	LS335	LS341
TYPE 3	1	Single	LS342	LS350	LS358	LS366	LS374	LS382
		Double	LS343	LS351	LS359	LS367	LS375	LS383
	2	Single	LS344	LS352	LS360	LS368	LS376	LS384
		Double	LS345	LS353	LS361	LS369	LS377	LS385
	3	Single	LS346	LS354	LS362	LS370	LS378	LS386
		Double	LS347	LS355	LS363	LS371	LS379	LS387
	4	Single	LS348	LS356	LS364	LS372	LS380	LS388
		Double	LS349	LS357	LS365	LS373	LS381	1 5389

			3' Model	4' Model	6' Model	8' Model	10' Model	12' Mode
	Width"	Ply	No.	No.	No.	No.	No.	No.
TYPE 4	1	Single	LS390	LS398	LS406	LS414	LS422	LS430
		Double	LS391	LS399	LS407	LS415	LS423	LS431
	2	Single	LS392	LS400	LS408	LS416	LS424	LS432
		Double	LS393	LS401	LS409	LS417	LS425	LS433
	3	Single	LS394	LS402	LS410	LS418	LS426	LS434
		Double	LS395	LS403	LS411	LS419	LS427	LS43!
	4	Single	LS396	LS404	LS412	LS420	LS428	LS430
		Double	LS397	LS405	LS413	LS421	LS429	LS43
TYPE 5	1	Single	LS438	LS446	LS454	LS462	LS470	LS47
		Double	LS439	LS447	LS455	LS463	LS471	LS47
	2	Single	LS440	LS448	LS456	LS464	LS472	LS48
		Double	LS441	LS449	LS457	LS465	LS473	LS48
	3	Single	LS442	LS450	LS458	LS466	LS474	LS48
		Double	LS443	LS451	LS459	LS467	LS475	LS48
	4	Single	LS444	LS452	LS460	LS468	LS476	LS48
		Double	LS445	LS453	LS461	LS469	LS477	LS48

B126