INSTRUMENTS & SCALES

ALL STAINLESS STEEL ELECTRONIC DIGITAL CALIPERS

- · Large LCD display provides easy-to-read numbers
- Precision adjustments for accurate measurements
- Hardened stainless steel head and body
- Lock screw to hold slide in position
- Linear accuracy: +/- .001" (.03 mm)
- Inch/millimeter conversion
- · Zero at any position
- ON/OFF button
- · Includes: Two 1.5V batteries, type LR44 and deluxe storage case with foam inserts



Model No.	Size	Measurement Range	Approximate Jaw Depth
TGZ370	6	0-6" (152 mm)	1-1/2" (38 mm) outside, 5/8" (16 mm) inside
TJZ861	8	0-8" (200 mm)	2" (50 mm) outside, 3/4" (19 mm) inside
THZ769	12	0-12" (305 mm)	2-7/8" (73 mm) outside, 7/8" (22.25 mm) inside

6" COOLANT PROOF ELECTRONIC DIGITAL CALIPER

- Resistant to dust, coolant liquids, oil and water spray
- Precision adjustments for accurate measurements
- · Large Protective Lens LCD display provides easy-to-read numbers
- 0-6" (152 mm) measurement range
 ABS Plastic head and stainless steel body
- Lock screw to hold slide in position
- Linear accuracy: +/- .001" (.03 mm)
- · Approximate jaw depth: 1-1/2" (38 mm) outside, 5/8" (16 mm) inside
- · Inch/millimeter conversion
- Zero at any position
- Automatic shut OFF
- · Includes two 1.5V batteries, type LR44 and a deluxe storage case with foam inserts

Model No. THZ768

ELECTRONIC DIGITAL MICROMETER

- Large LCD display provides easy-to-read numbers
- Carbide tipped measurement surfaces
- Inch/millimeter conversion
- · Thimble ratchet
- · Accurate to 5 decimal places
- Linear accuracy: +/- .0001" (.003 mm)
- Zero at any position
- Lock screw to hold mechanism in position
- · Automatic OFF button
- Includes: Calibration wrench, two 1.5V batteries, type LR44 and wooden storage case with foam insert





Model No.	No. Measurement Range Resolution		
IA388	0-1" (0-25 mm)	0.00005" (0.001 mm)	

CHAMP™ SQ MULTI-FUNCTIONAL INDUSTRIAL BENCH SCALES

- Capacities from 10 kg/25 lbs. to 250 kg/500 lbs.
- Stainless steel platter with painted steel frame
- RS232 interface standard with easy-to-read GMP data output: time, date, operator number, scale ID number, project number and name
- Weighing, parts counting, dynamic/animal weighing,
- percent weighing and checkweighing modes
- 2-line LCD display, Gross/Net/Tare function, auto-off timer, low battery warning, adjustable averaging and stability levels, retain zero data, auto-zero tracking, leveling feet and leveling bubble
- · 2-year warranty on parts and labour





LEGAL FOR TRADE

Model	Mfg.	Capacity	Graduation	Plat	form	Siz	е
No.	No.	lbs./kg	lbs./kg	W" x	D"	Х	Н"
HM318	CQ10R33	25/10	0.001/0.0005	12 x	12	Х	3.4
HM319	CQ25R33	50/25	0.002/0.001	12 x	12	Х	3.4
HM320	CQ50L33	100/50	0.005/0.002	18 x	18	Х	3.6
HM321	CQ100L33	200/100	0.01/0.005	18 x	18	Х	3.6
HM323	CQ250XL33	500/250	0.02/0.01	24 x	24	Х	5.8

DIGITAL COUNTING SCALE

- · Used for counting and quality checking
- High accuracy load cell
- Long life rechargeable battery
- 1/30,000 counting resolution
- Tare function
- Quantity set alarm
- Resolution: 0.4 g
- Graduation: 1 g
- · Capacity: 30 kg Model No. HX133

NOT LEGAL FOR TRADE



KILOTECH

LOW PROFILE BENCH SCALES

The ES Series design makes this low profile scale perfect for shipping, receiving and general bench applications. Easy two-button operation and large display guarantees accurate and unmistakable results. The 3-way mounting bracket (included) allows you to mount the indicator to front of scale base, above the base, or to any vertical surface.

- Display weight in kg, lbs, oz. or combined lb:oz*
- Stainless steel weighing platform and epoxy painted steel frame
- AC or battery powered operation

5 year warranty on parts and labour.

Includes 3-way mounting bracket and AC adapter.

Model	Mfg	Capacity	Readability	Platform Size
No.	No.	lbs./kg/oz.	lbs./g/oz.	L" x W" x H"
HN272	ES30R	66/30/1056	0.05/10g/0.5	12.2 x 10.8 x 1.5
HN273	ES50R	110/50/1760	0.05/20/1	12.2 x 10.8 x 1.5
HN274	ES50L	110/50/1760	0.05/20/1	20.5 x 15.7 x 3
HN275	ES100L	220/100/3520	0.01/50/2	20.5 x 15.7 x 3
HN276*	ES200L	440/200/7040	0.02/100/5	20.5 x 15.7 x 3

^{*} Lb:oz display not available on model HN276.



ELECTRONIC DIGITAL WEIGHING SCALES



- Suitable for a wide range of applications
- Four weighing modes: g, kg, lbs. and oz.
- Removable stainless steel platform
- Large LCD display (15/16"/25 mm)
- Battery or AC adapter operated (included)
- ABS enclosure



Model No. Mfg.No.		Capacity	Graduation
NOT LE	GAL FOR	TRADE	
HX142 HX143	SW5 SW10	2 kg/5 lbs.	1 g/0.002 lbs.
HX143	SW20	5 kg/10 lbs. 10 kg/20 lbs.	2 g/0.005 lbs. 5 g/0.01 lbs.
HX145	SW50	20 kg/50 lbs.	10 g/0.02 lbs.
LEGAL I	FOR TRAI	DE	
HX052	SW5	2 kg/5 lbs.	1 g/0.002 lbs.
HN278 HN279	SW10 SW20	5 kg/10 lbs. 10 kg/20 lbs.	2 g/0.005 lbs. 5 q/0.01 lbs.
HN280	SW50	20 kg/50 lbs.	10 g/0.01 lbs.





NOT LEGAL FOR TRADE

PORTABLE ELECTRONIC BALANCES

The Scout Pro is a portable balance designed to meet the most common weighing requirements in the lab, on the production line, in the field or the classroom. Features a large LCD, removable stainless steel pan and simple two-button operation. Weight display in g, kg, oz., lb, lb:oz.; and Troy ounce or pennyweight weight units for weighing precious materials.

Powered by 4 AA batteries (not included) or included AC adapter pack. Dimensions: 6.0" W x 2.2" H x 6.3" D. Weight: 1.8 lbs.

MULTIPLE WEIGHING MODES:

- · Parts counting
- · % weighing

- · Display hold for shipping applications
- · AC or battery power for portability

5 year warranty on parts and labour.

Model No.	Mfg. No.	Capacity (g)	Readability (g)	Pan Size
HX216	SP202	200	0.01	4.7" Diameter
HX218	SP401	400	0.1	4.7" Diameter
HM315	SP601	600	0.1	6.5" x 5.5"
HM065	76288-01 Security Device			
HM316	77256-01 Carrying Case			

UTILITY SCALE

This general purpose, portable weighing scale can be used in shipping and receiving areas. The large dual dial is easy to read from either the top or side position. The memory lock lever will hold the reading when dial is obscured by an oversized package.

NOT LEGAL FORTRADE

Model	Mfg.				Dimensions
No.	No.	Cap.	Х	Grad.	L" x W" x H"
HL933	P-250	250 lbs.	Х	1 oz.	13 1/2 x 11 x 2 3/4
HX655	P114S	114 kg	Χ	0.5 kg	13 1/2 x 11 x 2 3/4



B134

COMPACT ELECTRONIC SCALES

Ohaus compact scales are ideal when cost matters and dependable results are a must — perfect for use in the field, kitchen, or office. One-button operation, full capacity tare, LCD display, and operates on 3 AAA batteries (included) or with an optional AC adapter. Perfect as a postal scale for small parcels and letters.

Dimensions: 5.3" W x 7.6" D x 1.5" H. Weight: 1 lbs.

AC Power adapter included.

NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	х	Readability
HN218	CS200	200 g x 0.1 g	Х	0 lbs. 7.05 oz x 0.01 oz
HN219	CS2000	2000 g x 1.0 g	Х	4 lbs. 6.55 oz x 0.05 oz
HN220	CS5000	5000 g x 2.0 g	Χ	11 lbs. 0.4 oz x 0.1 oz
HL853	90524-66 Re	placement AC Power A	dapter	-

Displays results in g or combined lb:oz.

Battery power or AC operation.

2 year warranty on parts and labour.





LEGAL FOR TRADE	NOT LEGAL FOR TRADE					
Model	Model	Cap.	Beam Gra	aduation	Platform	Wt.
No.	No.	kg/lbs.	Metric /	Imperial	Size"	lbs.
HL960	HX147	50/100	2 kg x 20 g	5 lbs. x 1 oz	12 x 16	65
HL956	HX146	100/200	5 kg x 50 g	10 lbs. x 1 oz	12 x 16	88
HL963	HX148	300/600	25 kg x 100 g	50 lbs. x 4 oz	16 1/2 x 24	242
HL966	HX149	500/1200	25 kg x 100 g	50 lbs. x 8 oz	23 1/2 x 25	396

RECEIVING SCALES

These scales are heavy-duty, general purpose and are suitable for light industrial or shipping applications. The easy-to-read indicator is connected to the base by an 8' coiled cord that allows convenient remote placement. Large removable stainless steel platform allows for easy clean up. A keypad toggle allows easy kg/lb selection.

FEATURES:

- Kg/lbs. modes
- Programmable Auto-Off function
- Heavy-duty 8' coiled cord
- Removable stainless steel platform, 11.75" L x 12.25" W
- Zero, Tare and kg/lb (toggle) keys
 10 1/2" x 3 1/2" display
- Power supply: 6 AA alkaline batteries (not included) or 120 V AC adapter (included)
- One year warranty



Model No.	Mfg. No.	Capacity x Graduations
140.	140.	capacity x diaduations
HX632	KPS-50	110 lbs. x 0.1 lbs./50 kg x 0.05 kg
HX633	KPS-100	220 lbs. x 0.2 lbs./100 kg x 0.1 kg
PE111	KPS-180	400 lbs. x 0.2 lbs./180 kg x 100 g





HX632