TIME CLOCK

- Large, easy-to-read analog clock face
- LED display of year, month and date
- Automatic or manual printing
- Print window with light
- Automatically adjusts for Daylight Savings Time, short months, leap year and power outages
- Selectable for 4 digit imprint
- Built-in battery backup

SPECIFICATIONS:

Power Supply:	110/120 AC ±10% (50/60 Hz)
Power Consumption:	Normal 3 W, Max. 12 W
Ambient Temperature:	14°F - 113°F (-10°C - 45°C)
Humidity:	10% - 90% (no condensation)
Dimensions:	6 3/4" W x 6 1/4" D x 8" H
	150 x 172 x 165 (mm)
Weight:	6 lbs. (2.7 kg)

*Available in 220/240 V AC on special order only.

Model No.	Mfg. No.	Description
HN140	TCX-21E	English
HN163	TCX-21F	French

TIME CLOCK ACCESSORIES

- Card rack is adjusted for standard 8 1/4" long cards
- Fits 25 standard time cards
- Rack is adjustable to accommodate cards of different widths

Model No.	Description
HA004	Card Rack
HA001	1,000 Time Cards, English
HA020	1,000 Time Cards, French
HN141	Replacement Ribbon for Time Clock

HA004

WALL CLOCKS

BATTERY OPERATED

- 12" diameter round office wall clock
- 12/24 hour
- Black chrome frame

Model No. HT072

ELECTRIC CLOCK

- 12" diameter round office wall clock
- 12/24 hour
- Black frame

Model No. HX019

TIME CLOCK

- Manual or automatic print
- Selectable imprints: year (4 digit), month, date and time or notation
- Selectable print format: year, month and date or Julian date; day or date; AM/PM or 0-23 hours; regular minutes or 100th of an hour
- Right or left side printing
- Desk or wall mount
- Fast, easy set-up of date, time, print format, etc.
- Easy-to-replace ribbon cartridge
- Easy-to-read LCD display
- Calendar automatically adjusts for short months, leap year and Daylight Savings Time
- Quartz clock accuracy
- Built-in lithium battery backup protects clock and program data in the event of power failure
- Fast, quiet dot matrix printing
- Selectable notations: RCV'D, SENT, FAX'D, VOID, PAID, CFM'D APR'D, CMPL'D, ORIGN, FILE

SPECIFICATIONS:

Power Supply:	120 AC ±10%, 60 Hz
Power Consumption:	Normal 3W, Max. 6W
Ambient Temperature:	14°F-113°F (-10°C-45°C)
Humidity:	10% - 90% (no condensation)
Dimensions:	5.5" W x 6.5" D x 6" H
	150 x 140 x 165 (mm)
Weight:	4.2 lbs. (1.8 kg)

Model No.	Mfg. No.	Description
HN164	PIX-21E	English
HN165	PIX-21F	French

TAKE-A-NUMBER SYSTEM

- Provides fair, organized, efficient customer service
- Enhances the customer's perception of quality
- Assures customers their turn for service
- Used in supermarkets, retail stores, specialty shops, post offices, tourist information centres, travel bureaus, banks, hair salons, insurance companies, trade fairs, ticket sales offices, embassies, restaurants, and utility companies
- **Kit includes:**
    - 2-number segment display
    - Power supply (12 V AC)
    - 6 rolls of white tickets (4000/roll)
    - Dispenser (D900)
    - Counter Stand with sign
    - Push buttons and wires (1+, 1-)

Model No. OG421

REPLACEMENT TICKETS
Model No. OG442

TURN-O-MATIC®