

## NEW PRODUCTS

For tasks like asbestos abatement, mold remediation, and in-field packing, you need a tough tape.

Our rigorous-duty tapes stick for weeks, without fail, and leave no residue. When isolating rooms, or sealing walls, windows and doors, Shurtape helps deliver a solid barrier against particulate debris.

### PC 610

**Industrial Abatement Tape**  
Works in Cold Weather  
Aggressive Wet-Stick  
Superior Shear-to-Poly



10 mil Industrial grade cloth duct tape for sealing walls, doors and windows during mold/asbestos abatement and in rugged environments. Instant quick stick to poly-sheeting, metal and unpainted wood at temperatures as low as 25° F. Easy to use because it's easy to tear and it won't twist or curl off the roll.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	55
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### PC 629

**Contractor Grade**  
Excellent Cold  
Weather Performance  
New High-Tack Adhesive



11 mil Contractor grade cloth duct tape works at temperatures as cold as 25° F. Seals doors, walls and windows for mold and asbestos abatement. High-tack adhesive with superior shear performance grabs quickly and seals dependably. Does not twist or curl off the roll.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	65
Thickness (mils)	11.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

## COLORED DUCT

### PC 600

**Polycoated**  
**High Tack Adhesive**  
**Natural Rubber**  
**Adhesive**



General purpose use in industrial, plumbing, carpet, color coding, splicing, and other home and general repairs.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	9.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### PC 618

**Light Industrial**  
**Grade**  
**Poly Cotton**  
**Cloth Duct Tape**  
**Natural Rubber**  
**Adhesive**



To seal cartons, bind books, repair seats, bundle wires, color code, splice, repair, seal hatch covers and cargo doors in the shipping industry. Use as a condensation barrier in appliance assemblies. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	34, 53

### PC 619

**Specialty Grade**  
**Natural Rubber**  
**Adhesive**  
**Fluorescent Colors**



Waterproof backing, good conformability and range of fluorescent colors make this a natural fit for motorsports, motion picture and floral industries.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

1 ANSI No. 45.2.2	12 CID A-A 1492B	23 FAR 25.853	34 FSI 15/SDI 25	45 PPP-T-66E, Type I, Class 2*
2 ASME NQA-1	13 CID A-A-1586A	24 FSI 0/SDI 0	35 FSI 15/SDI 30	46 Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6
3 ASTM D 1974	14 CID A-A-1671B	25 FSI 0/SDI 5	36 FSI 25/SDI 50	47 Rule 41*
4 ASTM D 5330, Type II	15 CID A-A-1684C	26 FSI 5/SDI 5	37 L-T-80B	48 SAE-AMS-T-23397
5 ASTM D 5749, Type I, Class 2	16 CID A-A-1689B, Type I, Class 2	27 FSI 5/SDI 10	38 MIL-T-23397B AMDT 2 Type II*	49 Seal Classes A, B, C
6 ASTM D 5749, Type II, Grade B	17 CID A-A-1689B, Type II	28 FSI 5/SDI 15	39 NRC Guide 1.38	50 T-428
7 ASTM D 6123/D 6123M-97	18 CID A-A-180B, Type II, Grade A	29 FSI 10/SDI 10	40 PM-85 Tested	51 UL 181A-P/B-FX
8 ASTM D 5486M-99, Type III	19 CID A-A-180B, Type II, Grade B	30 FSI 10/SDI 35	41 PNS 8030-899-030	52 UL 1818-FX
9 ASTM D 5486M-99, Type IV	20 CID A-A-55809	31 FSI 15/SDI 40	42 PPP-T-0097E, Type II, Class A*	53 UL 723
10 ASTM D 5486M-99, Type V	21 CID A-A-883B, Type I	32 FSI 11/SDI 6	43 PPP-T-42C, Type I*	54 UL Listed
11 CID A-A-113D, Type I Class A	22 CID A-A-883B, Type II	33 FSI 15/SDI 20	44 PPP-T-60E, Type IV, Class I*	