

SPECIALTY GRADE DUCT

PC 21 F

**Cargo Pit
Cloth Duct Tape
Flame Retardant
Printed
F.A.R. 25.853 Compliant**



Used in the aerospace industry to seam, seal, and repair cargo compartment liners, cover pins and rivets. Adheres well to steel, fiberglass and plastic. HVAC where building codes require a flame retardant cloth duct tape. Flame retardant and F.A.R. 25.853 tested.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	40
Thickness (mils)	13.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	23, 28, 53

PC 623

**Nuclear Grade
Cloth Duct Tape
Natural Rubber Adhesive**



Used for a myriad of purposes in the construction, operation, and maintenance of nuclear power facilities. ASME NQA-1 tested.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	11.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	1, 2, 39

PC 624

**Premium Nuclear Grade
Cloth Duct Tape
Natural Rubber Adhesive**



13 mil premium grade cloth tape. Used for a myriad of purposes in the construction, operation and maintenance of nuclear power facilities. ASME NQA-1 tested.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	13.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	1, 2, 39

SF 683

**Metalized Backing
Printed
Natural Rubber Adhesive
HVAC**



Designed for air-tight and moisture-free sealing, seaming and joining aluminum-backed flex ducts and sealing metal ducts. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	11.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	25, 53

PC 857

**Printed
Natural Rubber Adhesive
UL 181B-FX Listed**



Used in the HVAC industry to seal, seam and join Class 1 Flex Duct. For use when the tensile strength and adhesion to stainless steel and polyethylene must meet or exceed the requirements of UL, flex duct manufacturers, and city and state building codes. UL 181B-FX listed.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	35, 52, 53

PC 667

**Specialty Grade
14-Day UV Resistant
Outdoor Cloth
Duct Tape**



Used for protective masking of non-painted surfaces of various materials such as steel, vinyl, aluminum and anodized metals. Used in plastering, stucco, concrete, pools, tile and synthetic surfaces when UV resistance is required.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	9.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

SHURTAPE

Distributor: **Dabco Industrial Supplies**
(800) 521-0049 - www.dabco.ca