

## VINYL COATED CLOTH

### PC 628

#### Gaffer's Tape

#### High Tack

#### Natural Rubber Adhesive



Perfectly suited for A/V, TV, photography, theatrical and motion picture industries. This weather resistant tape has good holding power for bundling wires, taping down lighting and props, and masking silk screen frames.

Tensile (lbs/in width)	46
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	12.0
Elongation (%)	5
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### P-672

#### Industrial Grade

#### Solventless Rubber-based Adhesive

#### ASME NQA-1 Tested



Vinyl-coated cloth tape is waterproof and industrial strength for sealing of containers, protection from welding splatter and other temporary repairs.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	12.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 44

### P-68

#### Embossed

#### Solventless Rubber-based Adhesive

#### ASTM D5486M, ANSI N45-2-2, T-428, PM-85 Tested



Waterproof backing, high tensile strength and abrasion resistance are key features of this gaffer's tape. Also works well in book binding and color coding applications. Available in a wide range of colors.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	57
Thickness (mils)	13.5
Elongation (%)	3
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 40, 44, 50

### P-691

#### Premium Grade

#### Solventless Rubber-based Adhesive

#### ASTM D5486M, CID A-A-1586A Tested



Premium grade cloth tape performs well over a wide range of temperatures. The waterproof backing and abrasion resistance make this tape ideally suited for sealing containers and rooms.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	9, 13, 44

### P-691 NSY

#### Specialty Grade

#### Solventless Rubber-based Adhesive

#### Naval Shipyard Approved



Specialty grade tape engineered to meet the Portsmouth Naval Shipyard specification 8030-899-030J. For use wherever an extra-strong, waterproof cloth tape is needed for holding, sealing and repairing.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 41, 44

### Lights, camera, action!

Our solventless, rubber-based, vinyl tape assures that the show will go on. It's great for bundling wires, taping props, securing lights or binding scripts. One of our grades is engineered to meet the most stringent shipyard specs and even protects from welding splatter. So when the show must go on, or the ship sails tomorrow, you can depend on Shurtape.

1 ANSI No. 45.2.2	12 CID A-A-1492B	23 FAR 25.853	34 FSI 15/SDI 25	45 PPP-T-66E, Type I, Class 2*
2 ASME NQA-1	13 CID A-A-1586A	24 FSI 0/SDI 0	35 FSI 15/SDI 30	46 Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6
3 ASTM D 1974	14 CID A-A-1671B	25 FSI 0/SDI 5	36 FSI 25/SDI 50	47 Rule 41*
4 ASTM D 5330, Type II	15 CID A-A-1684C	26 FSI 5/SDI 5	37 L-T-80B	48 SAE-AMS-T-23397
5 ASTM D 5749, Type I, Class 2	16 CID A-A-1689B, Type I, Class 2	27 FSI 5/SDI 10	38 MIL-T-23397B AMDT 2 Type II*	49 Seal Classes A, B, C
6 ASTM D 5749, Type II, Grade B	17 CID A-A-1689B, Type II	28 FSI 5/SDI 15	39 NRC Guide 1.38	50 T-428
7 ASTM D 6123/D 6123M-97	18 CID A-A-180B, Type II, Grade A	29 FSI 10/SDI 10	40 PM-85 Tested	51 UL 181A-P/B-FX
8 ASTM D 5486M-99, Type III	19 CID A-A-180B, Type II, Grade B	30 FSI 10/SDI 35	41 PNS 8030-899-030	52 UL 181B-FX
9 ASTM D 5486M-99, Type IV	20 CID A-A-55809	31 FSI 15/SDI 40	42 PPP-T-0097E, Type II, Class A*	53 UL 723
10 ASTM D 5486M-99, Type V	21 CID A-A-883B, Type I	32 FSI 11/SDI 6	43 PPP-T-42C, Type I*	54 UL Listed
11 CID A-A-113D, Type I Class A	22 CID A-A-883B, Type II	33 FSI 15/SDI 20	44 PPP-T-60E, Type IV, Class 1*	