

FOIL & PAPER COMPOSITE

AF 990

ASJ
Lined
High Tack



All Service Jacket tape used in cold and dual temperature systems to seal, seam, and join scrim reinforced pipe and duct insulation. Meets requirements of UL 723.

Tensile (lbs/in width)	50
Adhesion to Stainless Steel (oz/in width)	96
Thickness (mils)	8.0
Elongation (%)	2
Maximum Service Temperature (°F)	150
Applicable Specifications	53

AF 982

FSK
Lined
High Tack



All weather maximum strength Foil/Scrim/Kraft tape used to seal, seam, and join scrim reinforced pipe and duct insulation. Meets requirements of UL 723.

Tensile (lbs/in width)	35
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	6.8
Elongation (%)	1
Maximum Service Temperature (°F)	150
Applicable Specifications	53

UL 181B-FX FILM

DC 181

Printed OPP
Acrylic Adhesive
High Tack
UL 181B-FX Listed



Designed for use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork. UL 181B-FX listed.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	41
Thickness (mils)	3.0
Elongation (%)	50
Maximum Service Temperature (°F)	210
Applicable Specifications	52, 53

POLYETHYLENE FILM

PE 444

UV Resistant
Polyethylene Film Tape
Clean Removal



Used to mask surfaces during stucco application and painting. Special synthetic high-tack adhesive provides a watertight seal in severe environments and weather conditions. Residue free.

Tensile (lbs/in width)	18
Adhesion to Stainless Steel (oz/in width)	67
Thickness (mils)	7.0
Elongation (%)	100
Maximum Service Temperature (°F)	160
Applicable Specifications	—

PE 555

UV Resistant
Polyethylene Film Tape



Used to mask surfaces during stucco application and painting. Multi-purpose use for surface protection, color coding, splicing and seaming on pipe fitting covers. Waterproof, with excellent tear characteristics.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	67
Thickness (mils)	9.0
Elongation (%)	100
Maximum Service Temperature (°F)	160
Applicable Specifications	—

Proper preparation is key to any stucco job. Shurtape PE 444, PE 555, PC 622 and PC 667 make masking your job easier by sealing off windows and other openings securely. Our stucco tapes protect completely, creating a watertight seal in moisture rich environments. Even in prolonged sun exposure our tapes stick and stay, yet release without leaving residue. Shurtape – less clean-up and no touch-ups.

SHURTAPE

Distributor: **Dabco Industrial Supplies**
(800) 521-0049 - www.dabco.ca