

# PVC FILM

VP 410



**SPVC Line Set Tape**  
**Rubatex and Armaflex**  
**Seaming**



Used for floor, lane and aisle marking, color coding, wrapping line sets, wrapping Armaflex, and insulating air ducts and underground pipes. Use where resistance to moisture and humidity are required. Meets OSHA color coding requirements. Variety of colors available.

|                                                  |        |
|--------------------------------------------------|--------|
| <b>Tensile (lbs/in width)</b>                    | 18     |
| <b>Adhesion to Stainless Steel (oz/in width)</b> | 17     |
| <b>Thickness (mils)</b>                          | 5.5    |
| <b>Elongation (%)</b>                            | 150    |
| <b>Maximum Service Temperature (°F)</b>          | 176    |
| <b>Applicable Specifications</b>                 | 16, 45 |

VP 415



**SPVC Film**  
**Warning Stripe Tape**  
**Natural Rubber**  
**Adhesive**



Used for lane marking and identification of safety zones and hazard areas; wrapping and insulation of air ducts and underground pipes. Resistant to acids, alkalides, oils, moisture, humidity, corrosion and UV light.

|                                                  |        |
|--------------------------------------------------|--------|
| <b>Tensile (lbs/in width)</b>                    | 18     |
| <b>Adhesion to Stainless Steel (oz/in width)</b> | 17     |
| <b>Thickness (mils)</b>                          | 6.6    |
| <b>Elongation (%)</b>                            | 200    |
| <b>Maximum Service Temperature (°F)</b>          | 176    |
| <b>Applicable Specifications</b>                 | 16, 45 |

EV 57



**SPVC Film**  
**UL Listed Electrical Tape**



General purpose electrical tape for splicing, insulating and binding of wiring harnesses. High tensile strength and elongation with a non-corrosive adhesive.

|                                                  |        |
|--------------------------------------------------|--------|
| <b>Tensile (lbs/in width)</b>                    | 14     |
| <b>Adhesion to Stainless Steel (oz/in width)</b> | 16     |
| <b>Thickness (mils)</b>                          | 7.0    |
| <b>Elongation (%)</b>                            | 200    |
| <b>Maximum Service Temperature (°F)</b>          | 176    |
| <b>Applicable Specifications</b>                 | 20, 54 |



|                                 |                                   |                  |                                   |                                |
|---------------------------------|-----------------------------------|------------------|-----------------------------------|--------------------------------|
| 1 ANSI No. 45.2.2               | 12 CID A-A 1492B                  | 23 FAR 25.853    | 34 FSI 15/SDI 25                  | 45 PPP-T-66E, Type I, Class 2* |
| 2 ASME NQA-1                    | 13 CID A-A-1586A                  | 24 FSI 0/SDI 0   | 35 FSI 15/SDI 30                  | 46 Pressure Classes SMACNA     |
| 3 ASTM D 1974                   | 14 CID A-A-1671B                  | 25 FSI 0/SDI 5   | 36 FSI 25/SDI 50                  | 1/2, 1, 2, 3, 4, & 6           |
| 4 ASTM D 5330, Type II          | 15 CID A-A-1684C                  | 26 FSI 5/SDI 5   | 37 L-T-80B                        | 47 Rule 41*                    |
| 5 ASTM D 5749, Type I, Class 2  | 16 CID A-A-1689B, Type I, Class 2 | 27 FSI 5/SDI 10  | 38 MIL-T-23397B AMDT 2 Type II*   | 48 SAE-AMS-T-23397             |
| 6 ASTM D 5749, Type II, Grade B | 17 CID A-A-1689B, Type II         | 28 FSI 5/SDI 15  | 39 NRC Guide 1.38                 | 49 Seal Classes A, B, C        |
| 7 ASTM D 6123/D 6123M-97        | 18 CID A-A-180B, Type II, Grade A | 29 FSI 10/SDI 10 | 40 PM-85 Tested                   | 50 T-428                       |
| 8 ASTM D 5486M-99, Type III     | 19 CID A-A-180B, Type II, Grade B | 30 FSI 10/SDI 35 | 41 PNS 8030-899-030               | 51 UL 181A-P/B-FX              |
| 9 ASTM D 5486M-99, Type IV      | 20 CID A-A-55809                  | 31 FSI 15/SDI 40 | 42 PPP-T-0097E, Type II, Class A* | 52 UL 181B-FX                  |
| 10 ASTM D 5486M-99, Type V      | 21 CID A-A-883B, Type I           | 32 FSI 11/SDI 6  | 43 PPP-T-42C, Type I*             | 53 UL 723                      |
| 11 CID A-A-113D, Type I Class A | 22 CID A-A-883B, Type II          | 33 FSI 15/SDI 20 | 44 PPP-T-60E, Type IV, Class I*   | 54 UL Listed                   |