

## DOUBLE-COATED CLOTH

### DF 545

**Industrial Grade**  
**Double-faced**  
**Residue Free**



Holding carpet and pad at convention centers, arenas and hotels. Versatile adhesive system provides clean removal and superior adhesion to concrete, tile, hardwood flooring and other irregular surfaces. Poly laminate layer provides high tensile strength for demanding construction, convention and abatement applications.

<b>Tensile</b> (lbs/in width)	25
<b>Adhesion to Stainless Steel</b> (oz/in width)	45
<b>Thickness</b> (mils)	15.5
<b>Elongation</b> (%)	9
<b>Maximum Service Temperature</b> (°F)	200
<b>Applicable Specifications</b>	—

### DF 642

**Industrial Grade**  
**Double-faced**  
**Synthetic Rubber**  
**Adhesive**



Holding carpet and pad at convention centers, arenas and hotels. Also used to hold signs and dispensers for POP merchandising. Conformable to irregular surfaces and adheres to a variety of substrates.

<b>Tensile</b> (lbs/in width)	32
<b>Adhesion to Stainless Steel</b> (oz/in width)	29
<b>Thickness</b> (mils)	12.0
<b>Elongation</b> (%)	8
<b>Maximum Service Temperature</b> (°F)	225
<b>Applicable Specifications</b>	—

## DOUBLE-COATED FILM

### DP 050

**General Purpose**  
**Double-faced**  
**Solvent-based**  
**Acrylic Adhesive**



Ideally suited for splicing of corrugated board and other paper substrates where high shear is required. Maintains superior moisture resistance in high humidity environments.

<b>Tensile</b> (lbs/in width)	7.5
<b>Adhesion to Stainless Steel</b> (oz/in width)	65
<b>Thickness</b> (mils, without liner)	3.75
<b>Elongation</b> (%)	100
<b>Maximum Service Temperature</b> (°F)	—
<b>Applicable Specifications</b>	—

## TRANSFER ADHESIVE

### TA 450

**General Purpose**  
**Adhesive Transfer Tape**  
**Permanent Dry**



Mounting, holding, joining and splicing paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces in normal and severe environmental conditions and extreme temperatures. Resists humidity, most solvents and UV light. Features unsupported, siliconized release liner.

<b>Adhesion to Stainless Steel</b> (oz/in width)	25
<b>Adhesive Thickness</b> (mils)	1.8
<b>Liner Thickness</b> (mils)	5.0
<b>Maximum Service Temperature</b> (°F)	302
<b>Applicable Specifications</b>	—

### TG 356

**General Purpose**  
**Adhesive Transfer Tape**  
**Permanent Dry**



Mounting, holding, joining, and splicing paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces. Reverse wound on a 1" I.D. core with a siliconized release liner.

<b>Adhesion to Stainless Steel</b> (oz/in width)	25
<b>Adhesive Thickness</b> (mils)	1.8
<b>Liner Thickness</b> (mils)	5.5
<b>Maximum Service Temperature</b> (°F)	302
<b>Applicable Specifications</b>	—

At Shurtape we believe in doing the right job, the right way, the first time. We're ISO 9000 certified. We deliver 98 percent of stock orders within 72 hours. Less than one-half of one percent (<0.5%) of our orders are returned by customers. Quality, knowledge and commitment are what we're about. That's why our sales and technical staff work double time to meet your needs. Experience the Shurtape difference today.